

PRODUCT INFORMATION

Passenger Car Motor Oils DPF



0W-20 DPF-VW Ultra

Combisynth Motor Oil for Petrol and Diesel Engines

DESCRIPTION

REKTOL 0W-20 DPF-VW Ultra is particularly suitable for the most modern vehicles of the VW group. State-of-the-art fully synthetic and HC synthetic oils guarantee maximum fuel savings with the longest oil change intervals.

Not backwards compatible with other VW specifications!

THIS PRODUCT IS RECOMMENDED BY REKTOL IF THE FOLLOWING FILLING REQUIREMENTS ARE REQUIRED:

SAE 0W-20

API SP (RC)

ACEA C5

VW 508 00 und 509 00

BMW LL17FE+

ST JLR 51.5122 (Jaguar, Land Rover)

ILSAC GF-5

MB 229.71

Opel/Vauxhall OVO401547

Volvo VCC RBSO-2AE

Porsche C20

ADVANTAGES

- excellent wear protection
- outstanding oxidation- and temperature stability
- low friction losses
- optimum engine cleanliness due to excellent cleaning properties
- long oil changing intervals
- improved fuel efficiency

TYPICAL CHARACTERISTICS

Properties

Density at 15°C

CCS -35 °C

Pourpoint

Viscosity at 40 °C

Viscosity at 100 °C

Viscosity Index

Testing according

DIN 51757

ASTM-D 5293

DIN ISO 3016

DIN 51562

DIN 51562

DIN ISO 2909

Data Unit

0,846 g/ml

6000 cP

< -40 °C

42 mm²/sec

8,3 mm²/sec

178



PRODUCT INFORMATION

Passenger Car Motor Oils DPF



AVAILABLE PACKAGING



1L



4L



5L



20 L

Item-number: 106002411 106002414 106002416 106002420



60 L



205 L

Item-number: 106002430 106002436

The information in this product data sheet is based on over 127 years of experience of company Rektol GmbH & Co. KG. Our professional competence in the development and manufacturing of lubricants are based on the current state-of-the-art. Universally valid statements regarding the function of our lubricants are not possible, because the lubricant performance can be influenced by a series of factors. As a result the lubricant filling process, the exact purpose of use, the general operating conditions, the system degree of wear and the system contamination etc. must be taken into account in particular in engines, machinery and equipment. The data given in this product data sheet represents general, non-binding guideline values. No warranty expressed or implied is given concerning the properties. We recommend to consult our application engineer regarding the application conditions and requirements before the REKTOL lubricant is used. The user should test the functional suitability of our lubricants in the intended application and use the product with the corresponding care and responsibility according to the manufacturer's specifications. Our products undergo continuous improvements. We therefore reserve the right to change our product program, the products and their manufacturing processes as well as all details at any time and without warning. Please note: Our products may not be used in aircraft and spacecraft or parts thereof.

