

PRODUCT INFORMATION

Passenger Car Motor Oils DPF



0W-30 DPF-VW Ultra

Combisynth Motor Oil for Petrol and Diesel Engines

DESCRIPTION

REKTOL 0W-30 DPF-VW Ultra is a low SAPS smooth-running engine oil based on the latest HC and PAO synthesis technology. Specially developed for the requirements of modern gasoline and diesel engines from VW / Audi and Porsche. The low content of ash-forming substances (low SAPS) ensures optimal functionality of catalytic converters and exhaust gas aftertreatment systems such as DPF (diesel particulate filter) and SCR (AdBlue technology).

THIS PRODUCT IS RECOMMENDED BY REKTOL IF THE FOLLOWING FILLING REQUIREMENTS ARE REQUIRED:

SAE 0W-30
ACEA C3

Porsche C30
VW 504.00, 507.00

ADVANTAGES

- excellent wear protection
- outstanding oxidation- and temperature stability
- low friction losses
- optimum engine cleanliness due to excellent cleaning properties
- long oil changing intervals
- improved fuel efficiency

TYPICAL CHARACTERISTICS

Properties	Testing according	Data	Unit
Density at 15°C	DIN 51757	0,846	g/ml
CCS -35 °C	ASTM-D 5293	5600	cP
Pourpoint	DIN ISO 3016	< -40	°C
Viscosity at 40 °C	DIN 51562	69	mm ² /sec
Viscosity at 100 °C	DIN 51562	12	mm ² /sec
Viscosity Index	DIN ISO 2909	171	



PRODUCT INFORMATION

Passenger Car Motor Oils DPF



AVAILABLE PACKAGING



1L



4L



5L



20 L

Item-number: 106003611 106003614 106003616 106003620



60 L



205 L

Item-number: 106003630 106003636

The information in this product data sheet is based on over 127 years of experience of company Rektol GmbH & Co. KG. Our professional competence in the development and manufacturing of lubricants are based on the current state-of-the-art. Universally valid statements regarding the function of our lubricants are not possible, because the lubricant performance can be influenced by a series of factors. As a result the lubricant filling process, the exact purpose of use, the general operating conditions, the system degree of wear and the system contamination etc. must be taken into account in particular in engines, machinery and equipment. The data given in this product data sheet represents general, non-binding guideline values. No warranty expressed or implied is given concerning the properties. We recommend to consult our application engineer regarding the application conditions and requirements before the REKTOL lubricant is used. The user should test the functional suitability of our lubricants in the intended application and use the product with the corresponding care and responsibility according to the manufacturer's specifications. Our products undergo continuous improvements. We therefore reserve the right to change our product program, the products and their manufacturing processes as well as all details at any time and without warning. Please note: Our products may not be used in aircraft and spacecraft or parts thereof.

