

PRODUCT INFORMATION

Passenger Car Motor Oils GLOBAL



5W-20 Global Plus 5W-20 GF-5 Motor Oil for Petrol Engines

DESCRIPTION

REKTOL 5W-20 Global Plus is a low-friction motor oil based on advanced HC synthesis technology, suitable for passenger car petrol engines, vans, CUVs, SUVs and light commercial vehicles. Specially recommended for use in North American and Asian vehicles.

THIS PRODUCT IS RECOMMENDED BY REKTOL IF THE FOLLOWING FILLING REQUIREMENTS ARE REQUIRED:

SAE 5W-20

API SN/RC

ILSAC GF-5

Chrysler MS-6395

Fiat 9.55535-CR1

Ford WSS-M2C-925A/B, -945A/B

GM DX1-Gen2

GM 6094 M

Daihatsu, Honda, Hyundai, Isuzu, KIA,

Mazda, Mitsubishi, Nissan, Subaru,

Suzuki, Toyota, Lexus

ADVANTAGES

- excellent wear protection
- outstanding oxidation- and temperature stability
- low friction losses
- optimum engine cleanliness due to excellent cleaning properties
- long oil changing intervals
- improved fuel efficiency

TYPICAL CHARACTERISTICS

Properties

Density at 15°C

CCS -30 °C

Pourpoint

Viscosity at 40 °C

Viscosity at 100 °C

Viscosity Index

Testing according

DIN 51757

ASTM-D 5293

DIN ISO 3016

DIN 51562

DIN 51562

DIN ISO 2909

Data Unit

0,851 g/ml

5100 cP

< -35 °C

49 mm²/sec

8,8 mm²/sec

160



PRODUCT INFORMATION

Passenger Car Motor Oils GLOBAL



AVAILABLE PACKAGING



1L



4L



5L



20L

Item-number: 106052011 106052014 106052016 106052020



60L



205L

Item-number: 106052030 106052036

The information in this product data sheet is based on over 127 years of experience of company Rektol GmbH & Co. KG. Our professional competence in the development and manufacturing of lubricants are based on the current state-of-the-art. Universally valid statements regarding the function of our lubricants are not possible, because the lubricant performance can be influenced by a series of factors. As a result the lubricant filling process, the exact purpose of use, the general operating conditions, the system degree of wear and the system contamination etc. must be taken into account in particular in engines, machinery and equipment. The data given in this product data sheet represents general, non-binding guideline values. No warranty expressed or implied is given concerning the properties. We recommend to consult our application engineer regarding the application conditions and requirements before the REKTOL lubricant is used. The user should test the functional suitability of our lubricants in the intended application and use the product with the corresponding care and responsibility according to the manufacturer's specifications. Our products undergo continuous improvements. We therefore reserve the right to change our product program, the products and their manufacturing processes as well as all details at any time and without warning. Please note: Our products may not be used in aircraft and spacecraft or parts thereof.