

PRODUCT INFORMATION

Passenger Car Motor Oils DPF



5W-30 DPF-2/3 Plus 5W-30 GM DPF Motor Oil for Petrol and Diesel Engines

DESCRIPTION

REKTOL 5W-30 DPF-2/3 Plus is a low-friction motor oil based on advanced HC synthesis technology. Specially recommended for the use in Opel petrol and diesel engines.

The product fulfills the newest Longlife requirements and is therefore suitable for the longest oil change intervals.

THIS PRODUCT IS RECOMMENDED BY REKTOL IF THE FOLLOWING FILLING REQUIREMENTS ARE REQUIRED:

SAE 5W-30
ACEA C2/C3
API SN/CF
BMW Longlife 04
Fiat 9.55535-S3
PSA B712297
Ford M2C917-A,

MB 229.31, MB 229.51, MB 229.52, Opel
Dex2 Gen2: Opel engines after 2010,
backward compatible with GM-LL-A-025
and GM-LL-B-025
VW 502.00, 505.00, 505.01

ADVANTAGES

- excellent wear protection
- outstanding oxidation- and temperature stability
- low friction losses
- optimum engine cleanliness due to excellent cleaning properties
- long oil changing intervals
- improved fuel efficiency

TYPICAL CHARACTERISTICS

Properties

Density at 15°C
CCS -30 °C
Pourpoint
Viscosity at 40 °C
Viscosity at 100 °C
Viscosity Index

Testing according

DIN 51757
ASTM-D 5293
DIN ISO 3016
DIN 51562
DIN 51562
DIN ISO 2909

Data Unit

0,855 g/ml
5600 cP
< -35 °C
72 mm²/sec
11,8 mm²/sec
160

PRODUCT INFORMATION

Passenger Car Motor Oils DPF



AVAILABLE PACKAGING



Item-number: 106053111 106053114 106053116 106053120



Item-number: 106053130 106053136

The information in this product data sheet is based on over 127 years of experience of company Rektol GmbH & Co. KG. Our professional competence in the development and manufacturing of lubricants are based on the current state-of-the-art. Universally valid statements regarding the function of our lubricants are not possible, because the lubricant performance can be influenced by a series of factors. As a result the lubricant filling process, the exact purpose of use, the general operating conditions, the system degree of wear and the system contamination etc. must be taken into account in particular in engines, machinery and equipment. The data given in this product data sheet represents general, non-binding guideline values. No warranty expressed or implied is given concerning the properties. We recommend to consult our application engineer regarding the application conditions and requirements before the REKTOL lubricant is used. The user should test the functional suitability of our lubricants in the intended application and use the product with the corresponding care and responsibility according to the manufacturer's specifications. Our products undergo continuous improvements. We therefore reserve the right to change our product program, the products and their manufacturing processes as well as all details at any time and without warning. Please note: Our products may not be used in aircraft and spacecraft or parts thereof.