

PRODUCT INFORMATION

Truck Motor Oils



10W-40 Mega Truck

Motor Oil for Trucks and Commercial Vehicles

DESCRIPTION

REKTOL 10W-40 Mega Truck is a premium-quality low-friction motor oil for all-year use in heavily loaded commercial diesel engines of the Euro III, IV, and V technology. It ensures maximum oil change intervals up to 150,000 km (please observe manufacturer's instructions). Lower oil and fuel consumption reduces the running costs. Suited for fuels with a maximum sulphur content of 0.5 wt.-%.

THIS PRODUCT IS RECOMMENDED BY REKTOL IF THE FOLLOWING FILLING REQUIREMENTS ARE REQUIRED:

SAE 10W-40
API CI-4
ACEA E4, E7
Caterpillar ECF 2
Cummins 20078, 20077
DDC 93K215
Global DHD-1
Mack EO-M, EO-N

MAN M 3277, M 3377
MB 228.5
MTU Typ 3
Renault RXD, RLD-2
Volvo VDS-3
DAF
Scania LDF, LDF-2, LDF-3

TYPICAL CHARACTERISTICS

Properties

Density at 15°C
CCS -25 °C
Pourpoint
Viscosity at 40 °C
Viscosity at 100 °C
Viscosity Index
Base Number (TBN)

Testing according

DIN 51757
ASTM-D 5293
DIN ISO 3016
DIN 51562
DIN 51562
DIN ISO 2909
ASTM-D 2896

Data

0,860
5800
< -30
92
14
156
12

Unit

g/ml
cP
°C
mm²/sec
mm²/sec
mgKOH/g

AVAILABLE PACKAGING



PRODUCT INFORMATION

Truck Motor Oils



Item-number: 109104116 109104120



Item-number: 109104130 109104136

The information in this product data sheet is based on over 127 years of experience of company Rektol GmbH & Co. KG. Our professional competence in the development and manufacturing of lubricants are based on the current state-of-the-art. Universally valid statements regarding the function of our lubricants are not possible, because the lubricant performance can be influenced by a series of factors. As a result the lubricant filling process, the exact purpose of use, the general operating conditions, the system degree of wear and the system contamination etc. must be taken into account in particular in engines, machinery and equipment. The data given in this product data sheet represents general, non-binding guideline values. No warranty expressed or implied is given concerning the properties. We recommend to consult our application engineer regarding the application conditions and requirements before the REKTOL lubricant is used. The user should test the functional suitability of our lubricants in the intended application and use the product with the corresponding care and responsibility according to the manufacturer's specifications. Our products undergo continuous improvements. We therefore reserve the right to change our product program, the products and their manufacturing processes as well as all details at any time and without warning. Please note: Our products may not be used in aircraft and spacecraft or parts thereof.

