

PRODUCT INFORMATION

Truck Motor Oils



10W-40 Mega Truck LA

Motor Oil for Trucks and Commercial Vehicles

DESCRIPTION

REKTOL 10W-40 Mega Truck LA is Formulated for Euro IV and V diesel engines equipped with modern exhaust aftertreatment systems for example EGR, SCR and DPF. The low content of phosphor, sulphur and sulphate ash (Low SAPS) ensures reliable operation of the exhaust aftertreatment systems. This allows increased oil change intervals up to 150,000 km (please observe manufacturer's instructions). Suited for fuels with a maximum sulphur content of 0.5 wt.-%..

THIS PRODUCT IS RECOMMENDED BY REKTOL IF THE FOLLOWING FILLING REQUIREMENTS ARE REQUIRED:

SAE 10W-40
API CI-4, ACEA E6, E7
Cummins CES 20076, 20077
Mack EO-N
MAN M3477, 3271-1
MB 228.51
MTU Typ 3.1

Renault RDL-2
Volvo VDS-3
Caterpillar ECF-1a
Mack EO-M, MAN
Renault Truck RXD, RGD
Scania LA
DAF

TYPICAL CHARACTERISTICS

Properties	Testing according	Data	Unit
Density at 15°C	DIN 51757	0,857	g/ml
CCS -25 °C	ASTM-D 5293	5200	cP
Pourpoint	DIN ISO 3016	< -30	°C
Viscosity at 40 °C	DIN 51562	92	mm ² /sec
Viscosity at 100 °C	DIN 51562	14,2	mm ² /sec
Viscosity Index	DIN ISO 2909	160	

PRODUCT INFORMATION

Truck Motor Oils



AVAILABLE PACKAGING



Item-number: 109104216 109104220



Item-number: 109104230 109104236

The information in this product data sheet is based on over 127 years of experience of company Rektol GmbH & Co. KG. Our professional competence in the development and manufacturing of lubricants are based on the current state-of-the-art. Universally valid statements regarding the function of our lubricants are not possible, because the lubricant performance can be influenced by a series of factors. As a result the lubricant filling process, the exact purpose of use, the general operating conditions, the system degree of wear and the system contamination etc. must be taken into account in particular in engines, machinery and equipment. The data given in this product data sheet represents general, non-binding guideline values. No warranty expressed or implied is given concerning the properties. We recommend to consult our application engineer regarding the application conditions and requirements before the REKTOL lubricant is used. The user should test the functional suitability of our lubricants in the intended application and use the product with the corresponding care and responsibility according to the manufacturer's specifications. Our products undergo continuous improvements. We therefore reserve the right to change our product program, the products and their manufacturing processes as well as all details at any time and without warning. Please note: Our products may not be used in aircraft and spacecraft or parts thereof.