

PRODUCT INFORMATION

Passenger Car Motor Oils United



10W-60 United HP Super 10W-60 HP Combisynth Motor Oil for Petrol and Diesel Engines

DESCRIPTION

REKTOL 10W-40 United HP Super is a High Performance (HP) engine oil with a high levels of HC synthetic and fully synthetic base oils. This engine oil is ideally suited for year-round use in the most modern petrol and diesel engines. High engine cleanliness is guaranteed, even in turbocharger and catalytic converter operation as well as in multi-valve and diesel direct injection engines.

THIS PRODUCT IS RECOMMENDED BY REKTOL IF THE FOLLOWING FILLING REQUIREMENTS ARE REQUIRED:

SAE 10W-60
API SN/CF
ACEA A3/B4
PSA B71 2300

MB 229.1, MB 229.3
Renault RN 0700, 0710
VW 501.01, 502.00, 505.00
JASO MA

ADVANTAGES

- excellent wear protection
- outstanding oxidation- and temperature stability
- low friction losses
- optimum engine cleanliness due to excellent cleaning properties
- long oil changing intervals
- improved fuel efficiency

TYPICAL CHARACTERISTICS

Properties	Testing according	Data	Unit
Density at 15°C	DIN 51757	0,860	g/ml
CCS -25 °C	ASTM-D 5293	5950	cP
Pourpoint	DIN ISO 3016	< -30	°C
Viscosity at 40 °C	DIN 51562	185	mm ² /sec
Viscosity at 100 °C	DIN 51562	26	mm ² /sec
Viscosity Index	DIN ISO 2909	172	
Base Number [TBN]	ASTM-D 2896	10,2	mgKOH/g

PRODUCT INFORMATION

Passenger Car Motor Oils United



AVAILABLE PACKAGING



1L



4L



5L



20L

Item-number: 133106111 133106114 133106116 133106120



60L



205L

Item-number: 133106130 133106136

The information in this product data sheet is based on over 127 years of experience of company Rektol GmbH & Co. KG. Our professional competence in the development and manufacturing of lubricants are based on the current state-of-the-art. Universally valid statements regarding the function of our lubricants are not possible, because the lubricant performance can be influenced by a series of factors. As a result the lubricant filling process, the exact purpose of use, the general operating conditions, the system degree of wear and the system contamination etc. must be taken into account in particular in engines, machinery and equipment. The data given in this product data sheet represents general, non-binding guideline values. No warranty expressed or implied is given concerning the properties. We recommend to consult our application engineer regarding the application conditions and requirements before the REKTOL lubricant is used. The user should test the functional suitability of our lubricants in the intended application and use the product with the corresponding care and responsibility according to the manufacturer's specifications. Our products undergo continuous improvements. We therefore reserve the right to change our product program, the products and their manufacturing processes as well as all details at any time and without warning. Please note: Our products may not be used in aircraft and spacecraft or parts thereof.

