



REKTOL Mixed Fleet Motor oil 15W-40, 20W-50

Article number: 1331540 XX, 1332050 XX

Premium multi grade motor oils, suitable for use in passenger car petrol- and Diesel engines as well as truck Diesel engines, both turbocharged and non-turbocharged. Perfectly suitable as all-year use oils for the mixed vehicle fleet. The universal properties also enable the application in construction machines, stationary engines, tractors and various small machines.

Specification

SAE 15W-40, 20W-50, 20W-60
API SL/CF/CG-4

ACEA A3/B4, E3

Rektol Recommendation

Allison C4
MB 228.1, 228.3, 229.1
MAN 271, 3275
MTU Level 1, Level 2

Renault RD/RGD
Volvo VDS
VW 501.01, 505.00

User Benefits

- excellent shear stability
 - high oxidation stability
 - good viscosity-temperature behaviour
 - suitable for catalysts
 - advanced detergent- and dispersant properties
 - outstanding cold-start behaviour
 - high safety also under limited lubrication conditions
-

Typical characteristics

Density at 15°C	g/ml	DIN 51757	0,870	0,890
Flashpoint	°C	DIN ISO 2592	220	230
Pourpoint	°C	DIN ISO 3016	-28	-20
Viscosity at 40 °C	mm ² / sec	DIN 51562	100	165
Viscosity at 100 °C	mm ² / sec	DIN 51562	14	19
Viscosity Index		DIN ISO 2909	140	130

The information in this product data sheet is based on over 100 years of experience of company Rektol GmbH & Co. KG. Our professional competence in the development and manufacturing of lubricants are based on the current state-of-the-art. Universally valid statements regarding the function of our lubricants are not possible, because the lubricant performance can be influenced by a series of factors. As a result the lubricant filling process, the exact purpose of use, the general operating conditions, the system degree of wear and the system contamination etc. must be taken into account in particular in engines, machinery and equipment. The data given in this product data sheet represents general, non-binding guideline values. No warranty expressed or implied is given concerning the properties. We recommend to consult our application engineer regarding the application conditions and requirements before the REKTOL lubricant is used. The user should test the functional suitability of our lubricants in the intended application and use the product with the corresponding care and responsibility according to the manufacturer's specifications. Our products undergo continuous improvements. We therefore reserve the right to change our product program, the products and their manufacturing processes as well as all details at any time and without warning. Please note: Our products may not be used in aircraft and spacecraft or parts thereof.

Rektol GmbH & Co. KG

Am Kniep 2 • 34497 Korbach • Telefon: +49 (0) 5631-95300 • Telefax: +49 (0) 5631-953025

Internet: www.rektol.de • E-Mail: info@rektol.de