



REKTOL ATF 200

Automatic Transmission Fluid

Article number: 4000004 XX

Rektol ATF 200 is a high quality special transmission fluid, suitable for use in automatic gear boxes, hydrostatic drives and power steering units. It is the further development of ATF 100 gear oil with increased carrying capacity. Special EP-additives guarantee outstanding oxidation stability and excellent wear protection

Application note: Rektol ATF 200 is compatible and miscible with comparable lubricants. To exploit the advantages of ATF 200, it is recommended to take only ATF 200 when refilling.

Rektol Recommendations

Allison C-4	MAN 339 Z1
Cat TO-2	MB 236.1
Ford Mercon	TASA
GM Dexron II E, Dexron II D, Dexron II,	Voith 55.6335 (G607)
Dexron B, Typ A Suffix A	ZF TE-ML 02F, 03D, 04D, 09, 11B, 14A, 17C

User Benefits

- reliable protection against wear, sludge and corrosion
 - it retains original viscosity temperature behavior also by long change intervals
 - high thermal stability it does not foam under extreme load
 - is neutral towards metals and sealing materials
 - excellent shifting characteristics also at very low temperatures
-

Typical Characteristics

Density at 15°C	g/ml	DIN 51757	0,860
Flashpoint	°C	DIN ISO 2592	185
Pourpoint	°C	DIN ISO 3016	-45
Viscosity at 40 °C	mm ² / sec	DIN 51562	42
Viscosity at 100 °C	mm ² / sec	DIN 51562	7,8

The information in this product data sheet is based on over 100 years of experience of company Rektol GmbH & Co. KG. Our professional competence in the development and manufacturing of lubricants are based on the current state-of-the-art. Universally valid statements regarding the function of our lubricants are not possible, because the lubricant performance can be influenced by a series of factors. As a result the lubricant filling process, the exact purpose of use, the general operating conditions, the system degree of wear and the system contamination etc. must be taken into account in particular in engines, machinery and equipment. The data given in this product data sheet represents general, non-binding guideline values. No warranty expressed or implied is given concerning the properties. We recommend to consult our application engineer regarding the application conditions and requirements before the REKTOL lubricant is used. The user should test the functional suitability of our lubricants in the intended application and use the product with the corresponding care and responsibility according to the manufacturer's specifications. Our products undergo continuous improvements. We therefore reserve the right to change our product program, the products and their manufacturing processes as well as all details at any time and without warning. Please note: Our products may not be used in aircraft and spacecraft or parts thereof.

Rektol GmbH & Co. KG

Am Kniep 2 • 34497 Korbach • Telefon: +49 (0) 5631-95300 • Telefax: +49 (0) 5631-953025
Internet: www.rektol.de • E-Mail: info@rektol.de