

PRODUCT INFORMATION

Automatic Transmission Fluid



ATF 300

Automatic Transmission Fluid

DESCRIPTION

REKTOL ATF 300 is the further development of ATF 200. It is based on HC synthetic base oils as well as modified additives and is suitable for life time application (please observe manufacturer's instructions). Suited for use in automatic gear boxes, hydrostatic drives and power steering units.

THIS PRODUCT IS RECOMMENDED BY REKTOL IF THE FOLLOWING FILLING REQUIREMENTS ARE REQUIRED:

Allison C-4	MAN 339 V1, MAN 339 Z1
Cat TO-2	MB 236.1, MB 236.5
Ford Mercon	TASA
GM Dexron III H, Dexron III G	Voith 55.6335 (G607)
GM Dexron II E, Dexron II D, GM Dexron II, Dexron B	Volvo 97341
GM Typ A Suffix A	ZF TE-ML 02F, 03D, 04D, 09, 11B, 14A, 14B, 17C

TYPICAL CHARACTERISTICS

Properties	Testing according	Data	Unit
Density at 15°C	DIN 51757	0,858	g/ml
Pourpoint	DIN ISO 3016	< -40	°C
Viscosity at 40 °C	DIN 51562	40	mm ² /sec
Viscosity at 100 °C	DIN 51562	7,5	mm ² /sec
Viscosity Index	DIN ISO 2909	157	

PRODUCT INFORMATION

Automatic Transmission Fluid



AVAILABLE PACKAGING



Item-number: 400000511 400000516 400000520 400000530 400000536

The information in this product data sheet is based on over 127 years of experience of company Rektol GmbH & Co. KG. Our professional competence in the development and manufacturing of lubricants are based on the current state-of-the-art. Universally valid statements regarding the function of our lubricants are not possible, because the lubricant performance can be influenced by a series of factors. As a result the lubricant filling process, the exact purpose of use, the general operating conditions, the system degree of wear and the system contamination etc. must be taken into account in particular in engines, machinery and equipment. The data given in this product data sheet represents general, non-binding guideline values. No warranty expressed or implied is given concerning the properties. We recommend to consult our application engineer regarding the application conditions and requirements before the REKTOL lubricant is used. The user should test the functional suitability of our lubricants in the intended application and use the product with the corresponding care and responsibility according to the manufacturer's specifications. Our products undergo continuous improvements. We therefore reserve the right to change our product program, the products and their manufacturing processes as well as all details at any time and without warning. Please note: Our products may not be used in aircraft and spacecraft or parts thereof.