

PRODUCT INFORMATION

Automatic Transmission Fluid



ATF DSG

Direct Shift Gearbox Transmission Oil

DESCRIPTION

REKTOL ATF DSG is formulated for DSG (direct shift gearbox transmissions). Specially suitable for Audi- and VW direct shift gearbox transmissions, according to parts number TL 521 82...

THIS PRODUCT IS RECOMMENDED BY REKTOL IF THE FOLLOWING FILLING REQUIREMENTS ARE REQUIRED:

BMW DCTF-1, DTF-1, MTF LT-1, MTF LT-2,
BMW MTF-LT-5
Citroen / Peugeot 6DCT451
PSA Part Number 9734 S2
Ferrari TF DCT-F3
Fiat 9.55550-MZ-6, 9.55550-DA11
Ford WSS-M2C936-A, WSS-M2C200-D2
MB 236.21, 236.25
Mitsubishi Diamond Queen SSTF-1
Nissan Genuine Transmission Oil R35 Special

Porsche TF 0870
Renault BOT 450
Toyota LF
Volvo BOT 341, #1161838
VW / Audi / Seat / Skoda G 052 178,
G 052 182, TL 52 182, G 052 512,
G 052 513, G 052 529, G 052 726,
G 052 798, G 055 532, G 055 171
G 055 529
API GL-4

TYPICAL CHARACTERISTICS

Properties	Testing according	Data	Unit
Density at 15°C	DIN 51757	0,849	g/ml
Pourpoint	DIN ISO 3016	< -45	°C
Viscosity at 40 °C	DIN 51562	35	mm ² /sec
Viscosity at 100 °C	DIN 51562	7,1	mm ² /sec
Viscosity Index	DIN ISO 2909	171	



PRODUCT INFORMATION

Automatic Transmission Fluid



AVAILABLE PACKAGING



Item-number: 400000811 400000816 400000820 400000830 400000836

The information in this product data sheet is based on over 127 years of experience of company Rektol GmbH & Co. KG. Our professional competence in the development and manufacturing of lubricants are based on the current state-of-the-art. Universally valid statements regarding the function of our lubricants are not possible, because the lubricant performance can be influenced by a series of factors. As a result the lubricant filling process, the exact purpose of use, the general operating conditions, the system degree of wear and the system contamination etc. must be taken into account in particular in engines, machinery and equipment. The data given in this product data sheet represents general, non-binding guideline values. No warranty expressed or implied is given concerning the properties. We recommend to consult our application engineer regarding the application conditions and requirements before the REKTOL lubricant is used. The user should test the functional suitability of our lubricants in the intended application and use the product with the corresponding care and responsibility according to the manufacturer's specifications. Our products undergo continuous improvements. We therefore reserve the right to change our product program, the products and their manufacturing processes as well as all details at any time and without warning. Please note: Our products may not be used in aircraft and spacecraft or parts thereof.