

PRODUCT INFORMATION

Automatic Transmission Fluid



ATF CVT ASIA

Transmission Fluid for Continuously Variable Drives

DESCRIPTION

REKTOL ATF CVT ASIA formulated specially for the latest generation of CVT (Continuously Variable Transmission). Suitable for use in automatic gear boxes of Asian cars.

THIS PRODUCT IS RECOMMENDED BY REKTOL IF THE FOLLOWING FILLING REQUIREMENTS ARE REQUIRED:

Mazda JWS 3320

Mitsubishi NS-II, SP-III, CVTF-J1, Mitsubishi CVTF-J4 and J4+

Nissan NS-I, NS-II, NS-III

Subaru ECVT, Subaru iCVT, Subaru, iCVT FG, Subaru Lineartronic chain CVT and CVT II Fluid

Subaru Lineartronic High Torque (HT) DVT Fluid

Suzuki CVTF TC, Suzuki CVTF 3320, Suzuki CVT Green 1+2, Suzuki NS-2, Toyota CVTF TC,

Toyota CVTF FE

Daihatsu TC, Daihatsu Ammix CVTF DFE, Daihatsu Ammix CVT Fluid DC,

Daihatsu Ammix CVT Fluid DFC

Honda ATF-Z1, Honda HCF2, Honda HMMF (ohne Anfahrkupplung)

Hyundai / Kia CVT-J1, Hyundai / Kia SP-III

Idemitsu CVTS-EX1, JASO M 358

TYPICAL CHARACTERISTICS

Properties

Density at 15°C

Pourpoint

Viscosity at 40 °C

Viscosity at 100 °C

Viscosity Index

Testing according

DIN 51757

DIN ISO 3016

DIN 51562

DIN 51562

DIN ISO 2909

Data

0,848

< -45

34

7,0

170

Unit

g/ml

°C

mm²/sec

mm²/sec



PRODUCT INFORMATION

Automatic Transmission Fluid



AVAILABLE PACKAGING



Item-number.: 400001521 400001516 400001520 400001530 400001536

The information in this product data sheet is based on over 127 years of experience of company Rektol GmbH & Co. KG. Our professional competence in the development and manufacturing of lubricants are based on the current state-of-the-art. Universally valid statements regarding the function of our lubricants are not possible, because the lubricant performance can be influenced by a series of factors. As a result the lubricant filling process, the exact purpose of use, the general operating conditions, the system degree of wear and the system contamination etc. must be taken into account in particular in engines, machinery and equipment. The data given in this product data sheet represents general, non-binding guideline values. No warranty expressed or implied is given concerning the properties. We recommend to consult our application engineer regarding the application conditions and requirements before the REKTOL lubricant is used. The user should test the functional suitability of our lubricants in the intended application and use the product with the corresponding care and responsibility according to the manufacturer's specifications. Our products undergo continuous improvements. We therefore reserve the right to change our product program, the products and their manufacturing processes as well as all details at any time and without warning. Please note: Our products may not be used in aircraft and spacecraft or parts thereof.

