

PRODUCT INFORMATION

Gear Oils



85W-140 GL-5

Hypoid Gear Oil

DESCRIPTION

REKTOL 85W-140 GL-5 is a hypoid gear oil for highest performance requirements in hypoid axles of passenger cars, trucks, agricultural and construction machinery. It contains special additives which grant not only low-wear lubrication, but also an outstanding pressure absorption capacity. Suitable for use in heavily loaded axle drives of all types, for which a gear oil of the API GL5 specification is prescribed.

THIS PRODUCT IS RECOMMENDED BY REKTOL IF THE FOLLOWING FILLING REQUIREMENTS ARE REQUIRED:

SAE 85W-140	MB 235.0
API GL-5	MB 235.6
DAF (GL-5)	MIL-L-2105 C/D
Ford M2C9002-AA	Volvo 97310
MAN 342 M1	Scania STO 1.0
MAN 342 M2	

TYPICAL CHARACTERISTICS

Properties	Testing according	Data	Unit
Density at 15°C	DIN 51757	0,891	g/ml
Pourpoint	DIN ISO 3016	< -15	°C
Viscosity at 40 °C	DIN 51562	360	mm ² /sec
Viscosity at 100 °C	DIN 51562	28	mm ² /sec
Viscosity Index	DIN ISO 2909	105	

PRODUCT INFORMATION

Gear Oils



Contains Long-chain alkyl amine. May produce an allergic reaction.

AVAILABLE PACKAGING



1L



5L



20L

Item-number: 468851411 468851416 468851420



60L



205L

Item-number: 468851430 468851436

The information in this product data sheet is based on over 127 years of experience of company Rektol GmbH & Co. KG. Our professional competence in the development and manufacturing of lubricants are based on the current state-of-the-art. Universally valid statements regarding the function of our lubricants are not possible, because the lubricant performance can be influenced by a series of factors. As a result the lubricant filling process, the exact purpose of use, the general operating conditions, the system degree of wear and the system contamination etc. must be taken into account in particular in engines, machinery and equipment. The data given in this product data sheet represents general, non-binding guideline values. No warranty expressed or implied is given concerning the properties. We recommend to consult our application engineer regarding the application conditions and requirements before the REKTOL lubricant is used. The user should test the functional suitability of our lubricants in the intended application and use the product with the corresponding care and responsibility according to the manufacturer's specifications. Our products undergo continuous improvements. We therefore reserve the right to change our product program, the products and their manufacturing processes as well as all details at any time and without warning. Please note: Our products may not be used in aircraft and spacecraft or parts thereof.