



REKTOL SAE 75W-140 GL5 LS Getriebeöl

Article number: 1999999 XX



SINCE 1892

High performance gear oil for axle and transfer gearboxes, where API GL5 specification is required. The LS quality (Limited Slip additives) prevents from the unwanted slide and slip effect. Specially recommended for use in axles and limited slip differentials.

Performance Level

SAE 75W-140

API GL5

Limited Slip

Rektol also recommends this product, when the following specifications are required:

BMW 83222282583

BMW 83229407870

GM 12346140

CHRYSLER MS-8985

FORD M2C192-A

User Benefits

- highly adhesive and pressure-resistant lubrication film
- outstanding oxidation stability
- above average viscosity temperature behaviour
- outstanding-start properties
- excellent anti-wear properties

Typical Characteristics

Density at 15°C	g/ml	DIN 51757	0,816
Flash Point	°C	DIN ISO 2592	202
Pourpoint	°C	DIN ISO 3016	- 47
Viscosity at 40°C	mm ² / sec	DIN 51562	171
Viscosity at 100 °C	mm ² / sec	DIN 51562	26

Please observe operating instructions.

All above characteristics are average values and may vary due to production-related fluctuations.

Rektol GmbH & Co. KG

Am Kniep 2 • 34497 Korbach • Phone: +49 (0) 5631-95300

Fax: +49 (0) 5631-953025 • www.rektol.de • E-Mail: info@rektol.de