

PRODUCT INFORMATION

Gear Oils



75W-80 GL-4

Combisynt Special Gear Oil

DESCRIPTION

REKTOL 75W-80 GL-4 is a High-performance gear oil based on high-quality fully synthetic and HC synthetic components, in combination with advanced additive technology. Suitable for use in modern manual and transaxle transmissions. Please note: Not suitable for use in stepped automatic transmissions, DCT/DSG transmissions or CVT transmissions

THIS PRODUCT IS RECOMMENDED BY REKTOL IF THE FOLLOWING FILLING REQUIREMENTS ARE REQUIRED:

SAE 75W-80

API GL-4,

Truck:

DAF, Eaton,

MAN 341 VR, MAN 341 Z4,

MB 235.29, Voith Retarder,

Volvo 97307

Passenger car:

Alfa Romeo, BMW, Dacia, Fiat, Honda,

Mercedes Benz, Mini

PSA (Citroen, Peugeot), Renault, Seat,

Skoda, Smart, Volvo, VW -

Where the viscosity of 75W-80 and the performance of API GL4 are required..

TYPICAL CHARACTERISTICS

Properties

Density at 15°C

Pourpoint

Viscosity at 40 °C

Viscosity at 100 °C

Viscosity Index

Testing according

DIN 51757

DIN ISO 3016

DIN 51562

DIN 51562

DIN ISO 2909

Data Unit

0,858 g/ml

< -40 °C

54 mm²/sec

9,5 mm²/sec

161



PRODUCT INFORMATION

Gear Oils



Contains Long-chain alkyl amine. May produce an allergic reaction.

AVAILABLE PACKAGING



1L



5L



20L

Item-number: 477758011 477758016 477758020



60L



205L

Item-number: 477758030 477758036

The information in this product data sheet is based on over 127 years of experience of company Rektol GmbH & Co. KG. Our professional competence in the development and manufacturing of lubricants are based on the current state-of-the-art. Universally valid statements regarding the function of our lubricants are not possible, because the lubricant performance can be influenced by a series of factors. As a result the lubricant filling process, the exact purpose of use, the general operating conditions, the system degree of wear and the system contamination etc. must be taken into account in particular in engines, machinery and equipment. The data given in this product data sheet represents general, non-binding guideline values. No warranty expressed or implied is given concerning the properties. We recommend to consult our application engineer regarding the application conditions and requirements before the REKTOL lubricant is used. The user should test the functional suitability of our lubricants in the intended application and use the product with the corresponding care and responsibility according to the manufacturer's specifications. Our products undergo continuous improvements. We therefore reserve the right to change our product program, the products and their manufacturing processes as well as all details at any time and without warning. Please note: Our products may not be used in aircraft and spacecraft or parts thereof.

