

PRODUCT INFORMATION

Gear Oils



75W-90 GL-4/5

Combisynt Multigrade Gear Oil

DESCRIPTION

REKTOL 75W-90 GL-4/5 is a high-performance gear oil based on high-quality fully synthetic and HC synthetic components, in combination with advanced additive technology. Suitable for use in modern manual transmissions and axle drives. Please note: Not suitable for use in stepped automatic transmissions, DCT/DSG transmissions or CVT transmissions.

THIS PRODUCT IS RECOMMENDED BY REKTOL IF THE FOLLOWING FILLING REQUIREMENTS ARE REQUIRED:

SAE 75W-90	MB 235.1
API GL-4/5, MT1	MB 235.5
MAN 3343 M	MIL-L-2105 D
MAN 341 Z-2	MIL-L-2105 E
MAN 342 M-2	Scania STO 1:0
MB 235.8	Volvo 1273.10
MB 235.6	ZF TE-ML 01 (obsolete), 02B, 05A, 07A,
MB 235.0	08, 12A, 16B, 16C, 16D, 17A, 17B

TYPICAL CHARACTERISTICS

Properties

	Testing according	Data	Unit
Density at 15°C	DIN 51757	0,869	g/ml
Pourpoint	DIN ISO 3016	< -40	°C
Viscosity at 40 °C	DIN 51562	90	mm ² /sec
Viscosity at 100 °C	DIN 51562	14,5	mm ² /sec
Viscosity Index	DIN ISO 2909	167	

PRODUCT INFORMATION

Gear Oils



Contains Long-chain alkyl amine. May produce an allergic reaction.

AVAILABLE PACKAGING



1L



5L



20L

Item-number: 477759011 477759016 477759020



60L



205L

Item-number: 477759030 477759036

The information in this product data sheet is based on over 127 years of experience of company Rektol GmbH & Co. KG. Our professional competence in the development and manufacturing of lubricants are based on the current state-of-the-art. Universally valid statements regarding the function of our lubricants are not possible, because the lubricant performance can be influenced by a series of factors. As a result the lubricant filling process, the exact purpose of use, the general operating conditions, the system degree of wear and the system contamination etc. must be taken into account in particular in engines, machinery and equipment. The data given in this product data sheet represents general, non-binding guideline values. No warranty expressed or implied is given concerning the properties. We recommend to consult our application engineer regarding the application conditions and requirements before the REKTOL lubricant is used. The user should test the functional suitability of our lubricants in the intended application and use the product with the corresponding care and responsibility according to the manufacturer's specifications. Our products undergo continuous improvements. We therefore reserve the right to change our product program, the products and their manufacturing processes as well as all details at any time and without warning. Please note: Our products may not be used in aircraft and spacecraft or parts thereof.