



## REKTOL ProtectMix 11

Article number: 6990011 XX

---

Radiator coolant and antifreeze concentrate based on monoethylene glycol (color blue-green). Suitable as coolant, antifreeze and rust protection for year-round use in aluminum, light alloy and gray cast iron engines. It is free of nitrite, amine, phosphate compounds and protects against corrosion, prevents deposits and prevents foaming. Recommended use concentration: 50% REKTOL ProtectMix 11 and 50% softened water, with antifreeze protection to approx. -37 ° C. Depending on the type of vehicle, the contents of the cooling system should be changed every 2 to 3 years.

---

**This product is recommended when the following specifications are required:**

ASTM D 3306, ASTM D 4985, AFNOR NF R 15-601, BS6580:2010, SAE J1034, JIS K2234:2206, VW TL 774-C (11), MB 325.0, MAN 324 NF, Opel B 040 0240, MTU MTL 5048.

**Also recommended for the following vehicle manufacturers, where the performance No.11 is called for:**

MERCEDES-BENZ, VOLKSWAGEN, BMW, SMART, OPEL, LADA

### **Special properties**

- Guaranteed corrosion protection, also for non-ferrous metals and aluminum
- Safe frost protection
- Favorable evaporation properties
- Good miscibility
- Good elastomer compatibility (hoses and seals)
- Good action against deposits
- Prevents foaming

---

## Typical Characteristics

Density 20°C	g/ml	1,10
Colour		blaugrün
Flash Point	°C	< 109
Boiling Point	°C	> 195
Ignition Point	°C	400

## Security Alert: Harmful if swallowed



The information in this product data sheet is based on over 100 years of experience of company Rektol GmbH & Co. KG.

Our professional competence in the development and manufacturing of lubricants are based on the current state-of-the-art. Universally valid statements regarding the function of our lubricants are not possible, because the lubricant performance can be influenced by a series of factors. As a result the lubricant filling process, the exact purpose of use, the general operating conditions, the system degree of wear and the system contamination etc. must be taken into account in particular in engines, machinery and equipment. The data given in this product data sheet represents general, non-binding guideline values. No warranty expressed or implied is given concerning the properties. We recommend to consult our application engineer regarding the application conditions and requirements before the REKTOL lubricant is used. The user should test the functional suitability of our lubricants in the intended application and use the product with the corresponding care and responsibility according to the manufacturer's specifications. Our products undergo continuous improvements. We therefore reserve the right to change our product program, the products and their manufacturing processes as well as all details at any time and without warning. Please note: Our products may not be used in aircraft and spacecraft or parts thereof.

## Rektol GmbH & Co. KG

Am Kniep 2 • 34497 Korbach • Telefon: +49 (0) 5631-95300 • Telefax: +49 (0) 5631-953025

Internet: [www.rektol.de](http://www.rektol.de) • E-Mail: [info@rektol.de](mailto:info@rektol.de)